



802 WD Z2 M

Zone 2 ATEX certified industrial vacuum



Request a free
quotation

Download the
catalogue





802 WD Z2 M

Zone 2 ATEX certified industrial vacuum

802 WD Z2 is an ATEX certified industrial vacuum ideal for suction of liquids, even in hazardous environments that require Zone 2 ATEX certification.

The double filtration kit (wet or dry) supplied and the floating device, useful to stop the vacuum when container is full, allow the maximum durability of this powerful industrial vacuum, maintaining its best performances. Double ATEX certificate (machine and motor). Maintenance free motor, very silent and suitable for 24/7 continuous duty. Stainless steel container standard. Double stage dry filter with integrated self cleaning system. Integrated floating device and PPL filter for liquids. Integrated pressure relief valve.



Power	V	230 1~
Frequency	Hz	50
Power	kW	1,8
Depression	mmH2O	2300
Depression (continuous service)	mmH2O	1800
Airflow max	m3/h	250
Surface	cm2	8000
Filtration class (primary filter)	(IEC 60335-2-69)	M
Filter surface (HEPA filter)	cm2	27000
Filtration class (HEPA filter)	(EN1822)	H14
Air load on primary filter	m3/m2/h	312.00
Capacity	lt	80
Floating	-	SI
Suction inlet diameter	mm	80
Sound level	dB(A)	75
IP protection / Ins.Cl.	IP	65
Dimensions	cm	62 X 54 X 131 h.
Weight	kg	65
ATEX Zone	(Directive 94/9/CE)	2
Marking type	(Directive 94/9/CE)	II 3G